



Features ActivePure® Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The AirScrubber by Aerus® attaches directly to the HVAC system ductwork to reduce viruses, bacteria, and other contaminants in the ambient air and on surfaces while the HVAC fan is running. Patented ActivePure is an advanced surface and air purification technology. It has been proven to reduce up to 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure Technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2 – RNA Virus
- H1N1 Influenza
- H5N8 Influenza
- Murine Norovirus
- PhiX-174
- MS2 Bacteriophage
- MRSA
- E. coli
- Salmonella enterica
- Legionella pneumophila
- Clostridium difficile
- Bacillus globigii
- Erwinia herbicola
- Listeria monocytogenes
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Aspergillus versicolor
- Aspergillus niger endospores
- Methicillin-resistant Staphylococcus epidermis
- Staphylococcus epidermidis

THE BENEFITS

The AirScrubber by Aerus provides 24/7 surface decontamination and air purification without the use of ozone while the HVAC system fan is running. It is a proactive and effective solution for your home or small business.

- Uses the latest version of ActivePure Technology
- Provides 24/7 surface decontamination and air purification
- Reduces allergens and other contaminants
- Protects your heating and cooling system from potentially dangerous buildup



Air Scrubber

BY AERUS

WITH CERTIFIED SPACE TECHNOLOGY™

SPECIFICATIONS

Product Information	9960052 Model : A1013U (Ozone Free) Model A1013U meets California ozone emissions limit. CARB Certified. 9960051 Model : A1013P NOTE: This unit does not meet California requirements and cannot be shipped in California
Technology Included	ActivePure®
Electrical	Input Voltage: 24 Volts 1 Amp, 50/60 Hz; Current: 17 Watts *Conforms to UL STD 1598.
Mechanical	Distribution via air handler; Safety switch installed
Weight & Dimensions	3 pounds (1.2 kg.) 8.5" H x 8.5" W x 11" D (21.59cm H x 21.59cm W x 27.94cm D)
Cell Dimensions	2.25" H x 2.25" W x 9" D (5.71 cm H x 5.71 cm W x 22.86 cm D)
Operating Temperature	34 °F - 200 °F (1.6 °C - 93 °C)
Recommended Maximum Coverage in a Contiguous Space ¹	Up to 2,000 sq. ft. (185m ²) depending on occupant density and other factors.
Warranty	Limited 5 year warranty; 2 year warranty on ActivePure Cell & Bulb



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.